



DOSEEM RHZK9/A Self-contained Breathing Apparatus (SCBA)

DOSEEM RHZK series self-contained breathing apparatus (SCBA) is widely used in fire control, chemical, ship, oil, smelting, electric power, warehouse, laboratory, mine and other key departments for fire fighting, fire, gas, steam, and oxygen. It is a safe and effective for fire extinguishing and rescue. An ideal personal breathing protection device.



Optimized design, easy to use

DOSEEM RHZK9/A SCBA is one of the lightest fire breathing apparatus in the world. Innovatively developed an ergonomic backsheet with outstanding resistance to heat radiation, abrasion, tear and chemical resistance. Even in the harsh fire environment, DOSEEM RHZK9/A respirator is very comfortable to wear and stable. DOSEEM RHZK9/A not only obtained the latest CCCF mandatory fire certification and LA certification from the Ministry of Public Security, but also passed the EN137 1000°C high temperature flame test, which has excellent anti-wear and anti-heat radiation characteristics.

Enhanced backpack system

DOSEEM RHZK9/A integrates a strap that can be precisely attached to the backplate. Advanced extruded waterproof EVA harness material is protected by a CR rubber edge seal that resists tearing and wear. The wear-resistant and flame-retardant FR-TPE belt ensures a tight fit on the user's body even during large movements. The refined stainless steel metal lock makes the RHZK9/A quality more convenient and easy to use.

Pipeline integration, safe & reliable

In order to reduce the danger of being hooked and avoid physical damage,

pressure tube and the air supply tube are integrated in the backplane clamp of DOSEEM RHZK9/A backboard, which not only prevents thermal radiation impact, but also greatly enhances the safety of the enclosed space environment entering and working.

Easy maintenance

During service and maintenance, in order to minimize downtime and minimize costs, DOSEEM RHZK9/A incorporates a number of unique designs, all of which can be easily removed or reconnected from the backplane using simple tools. The strap is attached to the backing plate by a single adjustment of the innovative design. The snap connection of the primary pressure relief valve allows the pneumatic section to be quickly installed or removed from the respirator. The tubing can be quickly removed and cleaned from the backing plate.

Pressure head-up display device

It is convenient for firefighters to understand the pressure inside cylinder and avoid frequent checking of the pressure gauge. DOSEEM pressure head-up device consists of an electronic pressure gauge and a HUD. It uses a special protocol from DOSEEM to ensure the accuracy of data transmission and the uniqueness of pairing.

Best performance strap material


RHZK9/A uses state-of-the-art harness materials designed to withstand the high wear and tear that firefighters face every day. The product is equipped with a durable stainless steel lock and a long-life aramid blending belt, making it ideal for long wear and frequent use.



Article number: 01210

SCBA comprises a face mask, a HUD, a demand valve, an air cylinder and valve, a pressure reducing valve, a high pressure pipe, a medium pressure pipe, a backplate, a warning whistle and a pressure gauge.

Recommended field: Fire rescue



02076

Alarm whistle DSJBQ-1



02061

Mechanical pressure gauge DSFSB-1



02182

Self-locking cylinder valve KHF-30SA



01210



02001

Full face mask DSM-1



02056

HUD



02031

Demand Valve DSG-1



02084

9L Air cylinder



02233

Pressure reducer unit



02041

Backplate DSB-1

SCBA TECHNICAL DATAS

Model	RHZK9/A (01210)	Suction resistance	≤500Pa
Standard	GA124-2013	Expiratory resistance (25 times/min)	≤700Pa
Fulfill the standard	EN 137:2006; GB/16556-2007; NFPA 1981:2003	Expiratory resistance (40 times/min)	≤1000Pa
Capacity	9L	Operating temperature	-30~60℃
Storage capacity	2700L	The whole weight	12.4kg
Maximum air flow	≥1000L/min	Alarm intensity	≥90db
Working pressure	≤30MPa	Light work usage time	95min
Alarm pressure	5.5±0.5MPa	Moderate work usage time	60min
Static pressure in a mask cavity	≤500Pa	Heavy work usage time	40min

HUD TECHNICAL DATAS

Product name	Pressure head-up display device
Model	DSHUD-10 (Receiving end)
Explosion-proof grade	Ex ia IIC T4 Ga
Enclosure protection level	IP67
Operating temperature	-30℃~60℃
Weight	40g
Theoretical standby time	> 1 year
Continuous working time	> 200h
Power supply battery	1 section 3.0V CR2 lithium battery
Working time at low voltage	> 2h

MAINTENANCE

After each use of a SCBA it is necessary to ensure that it is stowed in a condition whereby it is ready again for immediate use. Follow the detailed instructions given by the manufacturer; they will generally include the following:

- Clean the set thoroughly;
- The full face mask should be cleaned with mild neutral detergent and disinfectant lotion, then thoroughly rinsed with clean water and dried naturally. Do not soak the mask in alcohol disinfectants for a long period of time and do not use steam for disinfection. Check that the fastenings are in good order;
- The surface of the components such as backplate, cylinder valve, pressure reducer, high pressure gauge, alarm and so on can be cleaned without plush soft cloth or gauze;
- Inspect the complete set for damage and any loose fittings;
- After use, the gas cylinder is wiped clean with soft cloth, and labelled it is the identification of empty bottle, so that it can be inflated in time. Fit a fully charged cylinder;
- Complete high pressure and low pressure tests disinfect the facemask;
- Re-stow the equipment in a ready-to-use condition and complete all use and test records;
- The maintenance of SCBA in full dry after the correct position into the packing box, stored in the air fresh, away from the heat source, without direct sunlight in the environment. It is forbidden to store in damp environment for a long time to prevent mildew.
- All equipment must be inspected at regular intervals, the inspection cycle is not more than one month, and always after use in practice or in an emergency. It should never be stowed when wet or dirty.

Manufacturer

Tel: +86-21-67329826

E-mail: info@doseem.com

Web: <https://www.doseem.com>

Add: No.599 Hong'an Rd, Jinshan, Shanghai



Wechat official



Official website